





**TP 250 - THREE-PHASE TRANSFORMER  
 400/230V - ELECTROSTATIC SHIELD -  
 250VA - IP00**



SKU: 32232  
 Référence technique: 28M23FD01000



**CARACTÉRISTIQUES TECHNIQUES:**

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 61558-2-1  
 Power : 250 VA  
 Primary voltage : 400V  
 Secondary voltage : 230V (Y+N)  
 :  
 Protection : IP00  
 Version : with electrostatic shield  
 Inrush current : less than or equal to 25 I<sub>n</sub>  
 Heatings : B (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 9,4 W  
 Load losses : 23 W  
 Voltage drop : 8,4 %  
 UCC : 7 %  
 Efficiency : 88,5 %

**DIMENSIONS:**

Dimensions (A x B x H) : 150 x 119 x 150 mm  
 Mounting centres (a x b) : 125 x 62 mm  
 Mounting diameter (ø) : 6x13 mm  
 Weight : 4,9 kg

**PROTECTION(S) RECOMMANDÉE(S):**

Primary 400V (aM fuse(s)) : 3 x 0,8A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 0,63A  
 Secondary 230V (C circuit breaker(s)) : 4 x 0,63A

**OPTIONS:**

Tropicalization