




TP 250 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - ELECTROSTATIC SHIELD - 250VA - IP00



SKU: 32234
 Référence technique: 28M23FDF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 250 VA
 Primary voltage : 400V
 Secondary voltage : 230V (Y+N)
 :
 Protection : IP00
 Version : with electrostatic shield & regulation tabs $\pm 5\%$
 Inrush current : less than or equal to 25 In
 Heatings : B (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 9,4 W
 Load losses : 23 W
 Voltage drop : 8,4 %
 UCC : 7 %
 Efficiency : 88,5 %

DIMENSIONS:

Dimensions (A x B x H) : 150 x 119 x 150 mm
 Mounting centres (a x b) : 125 x 62 mm
 Mounting diameter (\emptyset) : 6x13 mm
 Weight : 4,9 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,8A
 :
 Secondary 230V (gG fuse(s)) : 4 x 0,63A
 Secondary 230V (C circuit breaker(s)) : 4 x 0,63A

OPTIONS:

Tropicalization