





**TP 2500 - THREE-PHASE
TRANSFORMER 400/400V ±5% -
2,5KVA - IP00**



SKU: 31363
Référence technique: 28M36FFF0000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 2,5 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : with regulation tabs ±5%
Inrush current : less than or equal to 25 I_n
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 59 W
Load losses : 114 W
Voltage drop : 4,4 %
UCC : 3,2 %
Efficiency : 93,5 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 145 x 230 mm
Mounting centres (a x b) : 200 x 115 mm
Mounting diameter (∅) : 8x18 mm
Weight : 25 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 8A
:
Secondary 400V (gG fuse(s)) : 4 x 4A
Secondary 400V (C circuit breaker(s)) : 4 x 4A

OPTIONS:

Tropicalization