





**TP 2500 - THREE-PHASE
 TRANSFORMER 400/400V ±5% -
 ELECTROSTATIC SHIELD - 2,5KVA -
 IP00**



SKU: 31364
 Référence technique: 28M36FFF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 2,5 kVA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP00
 Version : with electrostatic shield & regulation tabs ±5%
 Inrush current : less than or equal to 25 I_n
 Heatings : F (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 59 W
 Load losses : 114 W
 Voltage drop : 4,4 %
 UCC : 3,2 %
 Efficiency : 93,5 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 145 x 230 mm
 Mounting centres (a x b) : 200 x 115 mm
 Mounting diameter (∅) : 8x18 mm
 Weight : 25 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 8A
 :
 Secondary 400V (gG fuse(s)) : 4 x 4A
 Secondary 400V (C circuit breaker(s)) : 4 x 4A

OPTIONS:

Tropicalization