



## TP 2500 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - ELECTROSTATIC SHIELD - 2,5KVA - IP00



SKU: 31364  
Référence technique: 28M36FFF1000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 2,5 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : with electrostatic shield & regulation tabs  $\pm 5\%$   
Inrush current : less than or equal to 25  $I_n$   
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 59 W  
Load losses : 114 W  
Voltage drop : 4,4 %  
UCC : 3,2 %  
Efficiency : 93,5 %

### DIMENSIONS:

Dimensions (A x B x H) : 240 x 145 x 230 mm  
Mounting centres (a x b) : 200 x 115 mm  
Mounting diameter ( $\emptyset$ ) : 8x18 mm  
Weight : 25 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 8A  
:  
Secondary 400V (gG fuse(s)) : 4 x 4A  
Secondary 400V (C circuit breaker(s)) : 4 x 4A

### OPTIONS:

Tropicalization