




## TP 2500 - THREE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 2,5KVA - IP00



SKU: 32362  
 Référence technique: 28M36FD01000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 61558-2-1  
 Power : 2,5 kVA  
 Primary voltage : 400V  
 Secondary voltage : 230V (Y+N)  
 :  
 Protection : IP00  
 Version : with electrostatic shield  
 Inrush current : less than or equal to 25 In  
 Heatings : F (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 59 W  
 Load losses : 114 W  
 Voltage drop : 4,4 %  
 UCC : 3,2 %  
 Efficiency : 93,5 %

### DIMENSIONS:

Dimensions (A x B x H) : 240 x 145 x 230 mm  
 Mounting centres (a x b) : 200 x 115 mm  
 Mounting diameter (∅) : 8x18 mm  
 Weight : 25 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 8A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 6A  
 Secondary 230V (C circuit breaker(s)) : 4 x 6A

### OPTIONS:

Tropicalization