




## TP 250 - ON REQUEST THREE-PHASE TRANSFORMER 250VA - IP00



SKU: TP250\_Specific  
Référence technique: 28M23...



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 250 VA  
Primary voltage : max. 1000V  
Secondary voltage : max. 1000V  
:  
Protection : IP00  
Version : specific  
Inrush current : less than or equal to 25 In  
Heatings : B (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 9,4 W  
Load losses : 23 W  
Voltage drop : 8,4 %  
UCC : 7 %  
Efficiency : 88,5 %

### DIMENSIONS:

Dimensions (A x B x H) : 150 x 119 x 150 mm  
Mounting centres (a x b) : 125 x 62 mm  
Mounting diameter (∅) : 6x13 mm  
Weight : 4,9 kg

### PROTECTION(S) RECOMMANDÉE(S):

:  
Other voltages : N.C.

### OPTIONS:

Electrostatic shield  
Thermal sensors (PTC, PT100, Twin-blades)  
Regulation tabs  
Primary and/or secondary coupling (star, delta, zig-zag)  
Dual primary  
Inrush current, frequency, heating, ambient temperature, specific altitude  
Tropicalization