





TP 315 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 315VA - IP00



SKU: 31243
 Référence technique: 28M25FFF0000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 315 VA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP00
 Version : with regulation tabs $\pm 5\%$
 Inrush current : less than or equal to 25 In
 Heatings : B (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 12,5 W
 Load losses : 26,3 W
 Voltage drop : 7,7 %
 UCC : 6,4 %
 Efficiency : 89,1 %

DIMENSIONS:

Dimensions (A x B x H) : 150 x 127 x 150 mm
 Mounting centres (a x b) : 125 x 72 mm
 Mounting diameter (\emptyset) : 6x13 mm
 Weight : 5,7 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 1A
 :
 Secondary 400V (gG fuse(s)) : 4 x 0,5A
 Secondary 400V (C circuit breaker(s)) : 4 x 0,5A

OPTIONS:

Tropicalization