





TP 315 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - 315VA - IP00



SKU: 32243
Référence technique: 28M25FDF0000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 315 VA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP00
Version : with regulation tabs $\pm 5\%$
Inrush current : less than or equal to 25 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 12,5 W
Load losses : 26,3 W
Voltage drop : 7,7 %
UCC : 6,4 %
Efficiency : 89,1 %

DIMENSIONS:

Dimensions (A x B x H) : 150 x 127 x 150 mm
Mounting centres (a x b) : 125 x 72 mm
Mounting diameter (\emptyset) : 6x13 mm
Weight : 5,7 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 1A
:
Secondary 230V (gG fuse(s)) : 4 x 0,8A
Secondary 230V (C circuit breaker(s)) : 4 x 0,8A

OPTIONS:

Tropicalization