





**TP 3150 - THREE-PHASE
TRANSFORMER 400/400V $\pm 5\%$ -
ELECTROSTATIC SHIELD - 3,15KVA -
IP00**



SKU: 31384
Référence technique: 28M38FFF1000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 3,15 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : with electrostatic shield & regulation tabs $\pm 5\%$
Inrush current : less than or equal to 25 I_n
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 73 W
Load losses : 151 W
Voltage drop : 4,6 %
UCC : 3,4 %
Efficiency : 93,4 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 160 x 280 mm
Mounting centres (a x b) : 250 x 100 mm
Mounting diameter (\emptyset) : 8,5x20 mm
Weight : 31 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 10A
:
Secondary 400V (gG fuse(s)) : 4 x 5A
Secondary 400V (C circuit breaker(s)) : 4 x 5A

OPTIONS:

Tropicalization