





**TP 3150 - THREE-PHASE  
TRANSFORMER 400/230V -  
ELECTROSTATIC SHIELD - 3,15KVA -  
IP00**



SKU: 32382  
Référence technique: 28M38FD01000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 3,15 kVA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP00  
Version : with electrostatic shield  
Inrush current : less than or equal to 25 In  
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 73 W  
Load losses : 151 W  
Voltage drop : 4,6 %  
UCC : 3,4 %  
Efficiency : 93,4 %

### DIMENSIONS:

Dimensions (A x B x H) : 300 x 160 x 280 mm  
Mounting centres (a x b) : 250 x 100 mm  
Mounting diameter (∅) : 8,5x20 mm  
Weight : 31 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 10A  
:  
Secondary 230V (gG fuse(s)) : 4 x 8A  
Secondary 230V (C circuit breaker(s)) : 4 x 8A

### OPTIONS:

Tropicalization