





## TP 400 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - 400VA - IP00



SKU: 32263  
 Référence technique: 28M26FDF0000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 61558-2-1  
 Power : 400 VA  
 Primary voltage : 400V  
 Secondary voltage : 230V (Y+N)  
 :  
 Protection : IP00  
 Version : with regulation tabs  $\pm 5\%$   
 Inrush current : less than or equal to 25 In  
 Heatings : B (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 13,1 W  
 Load losses : 33,6 W  
 Voltage drop : 7,7 %  
 UCC : 6,4 %  
 Efficiency : 89,5 %

### DIMENSIONS:

Dimensions (A x B x H) : 180 x 120 x 175 mm  
 Mounting centres (a x b) : 150 x 65 mm  
 Mounting diameter (Ø) : 8x18 mm  
 Weight : 6,8 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,25A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 1A  
 Secondary 230V (C circuit breaker(s)) : 4 x 1A

### OPTIONS:

Tropicalization