




TP 400 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - 400VA - IP00



SKU: 32263
 Référence technique: 28M26FDF0000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 400 VA
 Primary voltage : 400V
 Secondary voltage : 230V (Y+N)
 :
 Protection : IP00
 Version : with regulation tabs $\pm 5\%$
 Inrush current : less than or equal to 25 In
 Heatings : B (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 13,1 W
 Load losses : 33,6 W
 Voltage drop : 7,7 %
 UCC : 6,4 %
 Efficiency : 89,5 %

DIMENSIONS:

Dimensions (A x B x H) : 180 x 120 x 175 mm
 Mounting centres (a x b) : 150 x 65 mm
 Mounting diameter (\emptyset) : 8x18 mm
 Weight : 6,8 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,25A
 :
 Secondary 230V (gG fuse(s)) : 4 x 1A
 Secondary 230V (C circuit breaker(s)) : 4 x 1A

OPTIONS:

Tropicalization