




## TP 4000 - THREE-PHASE TRANSFORMER 400/400V - ELECTROSTATIC SHIELD - 4KVA - IP00



SKU: 31392  
Référence technique: 28M39FF01000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 4 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : with electrostatic shield  
Inrush current : less than or equal to 25 In  
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 85 W  
Load losses : 161 W  
Voltage drop : 3,9 %  
UCC : 2,9 %  
Efficiency : 94,2 %

### DIMENSIONS:

Dimensions (A x B x H) : 300 x 170 x 280 mm  
Mounting centres (a x b) : 250 x 110 mm  
Mounting diameter (ø) : 8,5x20 mm  
Weight : 37 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 12A  
:  
Secondary 400V (gG fuse(s)) : 4 x 6A  
Secondary 400V (C circuit breaker(s)) : 4 x 6A

### OPTIONS:

Tropicalization