



**TP 4000 - THREE-PHASE  
TRANSFORMER 400/230V ±5% - 4KVA  
- IP00**



SKU: 32393  
Référence technique: 28M39FDF0000

### **CARACTÉRISTIQUES TECHNIQUES:**

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 4 kVA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP00  
Version : with regulation tabs ±5%  
Inrush current : less than or equal to 25 I<sub>n</sub>  
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 85 W  
Load losses : 161 W  
Voltage drop : 3,9 %  
UCC : 2,9 %  
Efficiency : 94,2 %

### **DIMENSIONS:**

Dimensions (A x B x H) : 300 x 170 x 280 mm  
Mounting centres (a x b) : 250 x 110 mm  
Mounting diameter (∅) : 8,5x20 mm  
Weight : 37 kg

### **PROTECTION(S) RECOMMANDÉE(S):**

Primary 400V (aM fuse(s)) : 3 x 12A  
:  
Secondary 230V (gG fuse(s)) : 4 x 10A  
Secondary 230V (C circuit breaker(s)) : 4 x 10A

### **OPTIONS:**

Tropicalization