





**TP 500 - THREE-PHASE TRANSFORMER
400/400V - ELECTROSTATIC SHIELD -
500VA - IP00**



SKU: 31272
Référence technique: 28M27FF01000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 500 VA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : with electrostatic shield
Inrush current : less than or equal to 25 I_n
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 15,3 W
Load losses : 40,3 W
Voltage drop : 7,45 %
UCC : 6,3 %
Efficiency : 90 %

DIMENSIONS:

Dimensions (A x B x H) : 180 x 125 x 175 mm
Mounting centres (a x b) : 150 x 70 mm
Mounting diameter (∅) : 8x18 mm
Weight : 7,5 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 1,6A
:
Secondary 400V (gG fuse(s)) : 4 x 0,8A
Secondary 400V (C circuit breaker(s)) : 4 x 0,8A

OPTIONS:

Tropicalization