




## TP 500 - THREE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 500VA - IP00



SKU: 32272  
Référence technique: 28M27FD01000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 500 VA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP00  
Version : with electrostatic shield  
Inrush current : less than or equal to 25 I<sub>n</sub>  
Heatings : B (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 15,3 W  
Load losses : 40,3 W  
Voltage drop : 7,45 %  
UCC : 6,3 %  
Efficiency : 90 %

### DIMENSIONS:

Dimensions (A x B x H) : 180 x 125 x 175 mm  
Mounting centres (a x b) : 150 x 70 mm  
Mounting diameter (∅) : 8x18 mm  
Weight : 7,5 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 1,6A  
:  
Secondary 230V (gG fuse(s)) : 4 x 1,25A  
Secondary 230V (C circuit breaker(s)) : 4 x 1,25A

### OPTIONS:

Tropicalization