




TP 5000 - THREE-PHASE TRANSFORMER 400/400V - 5KVA - IP00



SKU: 31401
 Référence technique: 28B40FF00000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 5 kVA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP00
 Version : Transformer (standard)
 Inrush current : less than or equal to 25 In
 Heatings : F (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 85 W
 Load losses : 228 W
 Voltage drop : 4,35 %
 UCC : 4,5 %
 Efficiency : 94,1 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 170 x 280 mm
 Mounting centres (a x b) : 250 x 110 mm
 Mounting diameter (ø) : 8,5x20 mm
 Weight : 41 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 16A
 :
 Secondary 400V (gG fuse(s)) : 4 x 8A
 Secondary 400V (C circuit breaker(s)) : 4 x 8A

OPTIONS:

Tropicalization