





**TP 5000 - THREE-PHASE
TRANSFORMER 400/400V ±5% - 5KVA
- IP00**



SKU: 31403
Référence technique: 28B40FFF0000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 5 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : Transformer (regulation tabs ±5%)
Inrush current : less than or equal to 25 In
Heatings : F (IEC 60085)
Max. ambient T° : 40°C
No load losses : 85 W
Load losses : 228 W
Voltage drop : 4,35 %
UCC : 4,5 %
Efficiency : 94,1 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 170 x 280 mm
Mounting centres (a x b) : 250 x 110 mm
Mounting diameter (∅) : 8,5x20 mm
Weight : 41 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 16A
:
Secondary 400V (gG fuse(s)) : 4 x 8A
Secondary 400V (C circuit breaker(s)) : 4 x 8A

OPTIONS:

Tropicalization