






**TP 5000 - THREE-PHASE  
TRANSFORMER 400/400V ±5% - 5KVA  
- IP00**



SKU: 31403  
Référence technique: 28B40FFF0000



### **CARACTÉRISTIQUES TECHNIQUES:**

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 5 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : Transformer (regulation tabs ±5%)  
Inrush current : less than or equal to 25 In  
Heatings : F (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 85 W  
Load losses : 228 W  
Voltage drop : 4,35 %  
UCC : 4,5 %  
Efficiency : 94,1 %

### **DIMENSIONS:**

Dimensions (A x B x H) : 300 x 170 x 280 mm  
Mounting centres (a x b) : 250 x 110 mm  
Mounting diameter (∅) : 8,5x20 mm  
Weight : 41 kg

### **PROTECTION(S) RECOMMANDÉE(S):**

Primary 400V (aM fuse(s)) : 3 x 16A  
:  
Secondary 400V (gG fuse(s)) : 4 x 8A  
Secondary 400V (C circuit breaker(s)) : 4 x 8A

### **OPTIONS:**

Tropicalization