



TP 5000 - ON REQUEST THREE-PHASE TRANSFORMER 5KVA - IP00



SKU: TP5000_Specific
Référence technique: 28B40...



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 5 kVA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP00
Version : Transformer (specific)
Inrush current : less than or equal to 25 In
Heatings : F (IEC 60085)
Max. ambient T° : 40°C
No load losses : 85 W
Load losses : 228 W
Voltage drop : 4,35 %
UCC : 4,5 %
Efficiency : 94,1 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 170 x 280 mm
Mounting centres (a x b) : 250 x 110 mm
Mounting diameter (∅) : 8,5x20 mm
Weight : 41 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization