




TP 6300 - ON REQUEST THREE-PHASE TRANSFORMER 6,3KVA - IP00



SKU: TP6300_Specific
 Référence technique: 28B41...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 6,3 kVA
 Primary voltage : max. 1000V
 Secondary voltage : max. 1000V
 :
 Protection : IP00
 Version : Transformer (specific)
 Inrush current : less than or equal to 25 In
 Heatings : F (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 110 W
 Load losses : 240 W
 Voltage drop : 3,7 %
 UCC : 3,8 %
 Efficiency : 94,7 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 190 x 280 mm
 Mounting centres (a x b) : 250 x 130 mm
 Mounting diameter (∅) : 8,5x20 mm
 Weight : 49 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Primary and/or secondary coupling (star, delta, zig-zag)
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization