





## TP 800 - THREE-PHASE TRANSFORMER 400/400V - ELECTROSTATIC SHIELD - 800VA - IP00



SKU: 31302  
 Référence technique: 28M30FF01000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 61558-2-1  
 Power : 800 VA  
 Primary voltage : 400V  
 Secondary voltage : 400V (Y+N)  
 :  
 Protection : IP00  
 Version : with electrostatic shield  
 Inrush current : less than or equal to 25 I<sub>n</sub>  
 Heatings : B (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 22 W  
 Load losses : 59,6 W  
 Voltage drop : 6,9 %  
 UCC : 5,5 %  
 Efficiency : 90,7 %

### DIMENSIONS:

Dimensions (A x B x H) : 180 x 140 x 175 mm  
 Mounting centres (a x b) : 150 x 85 mm  
 Mounting diameter (∅) : 8x18 mm  
 Weight : 10,2 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 2,5A  
 :  
 Secondary 400V (gG fuse(s)) : 4 x 1,25A  
 Secondary 400V (C circuit breaker(s)) : 4 x 1,25A

### OPTIONS:

Tropicalization