



TP 800 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - ELECTROSTATIC SHIELD - 800VA - IP00



SKU: 32304
Référence technique: 28M30FDF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 800 VA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP00
Version : with electrostatic shield & regulation tabs $\pm 5\%$
Inrush current : less than or equal to 25 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 22 W
Load losses : 59,6 W
Voltage drop : 6,9 %
UCC : 5,5 %
Efficiency : 90,7 %

DIMENSIONS:

Dimensions (A x B x H) : 180 x 140 x 175 mm
Mounting centres (a x b) : 150 x 85 mm
Mounting diameter (\emptyset) : 8x18 mm
Weight : 10,2 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 2,5A
:
Secondary 230V (gG fuse(s)) : 4 x 2A
Secondary 230V (C circuit breaker(s)) : 4 x 2A

OPTIONS:

Tropicalization