




TPA 10000 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 10KVA - IP00



SKU: 33433
Référence technique: A37B43FFF0000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 10 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : Transformer (regulation tabs $\pm 5\%$)
Inrush current : less than or equal to 12 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 120 W
Load losses : 575 W
Voltage drop : 5,4 %
UCC : 6 %
Efficiency : 93,5 %

DIMENSIONS:

Dimensions (A x B x H) : 420 x 265 x 350 mm
Mounting centres (a x b) : 330 x 235 mm
Mounting diameter (\emptyset) : 11x22 mm
Weight : 57 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 16A
:
Secondary 400V (gG fuse(s)) : 4 x 16A
Secondary 400V (C circuit breaker(s)) : 4 x 16A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels