




## TPA 10000 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 10KVA - IP00



SKU: 33433  
Référence technique: A37B43FFF0000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 10 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : Transformer (regulation tabs  $\pm 5\%$ )  
Inrush current : less than or equal to 12 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 120 W  
Load losses : 575 W  
Voltage drop : 5,4 %  
UCC : 6 %  
Efficiency : 93,5 %

### DIMENSIONS:

Dimensions (A x B x H) : 420 x 265 x 350 mm  
Mounting centres (a x b) : 330 x 235 mm  
Mounting diameter ( $\emptyset$ ) : 11x22 mm  
Weight : 57 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 16A  
:  
Secondary 400V (gG fuse(s)) : 4 x 16A  
Secondary 400V (C circuit breaker(s)) : 4 x 16A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels