



**TPA 125000 - THREE-PHASE  
TRANSFORMER 400/400V -  
ELECTROSTATIC SHIELD - 125KVA -  
IP00**



SKU: 33542  
Référence technique: S37B54FF01000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 125 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : with electrostatic shield  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 800 W  
Load losses : 2850 W  
Voltage drop : 2,2 %  
UCC : 4,7 %  
Efficiency : 97,2 %

### DIMENSIONS:

Dimensions (A x B x H) : 640 x 500 x 600 mm  
Mounting centres (a x b) : 460 x 320 mm  
Mounting diameter (Ø) : 14 mm  
Weight : 425 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 200A  
:  
Secondary 400V (gG fuse(s)) : 4 x 200A  
Secondary 400V (C circuit breaker(s)) : 4 x 200A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels