



**TPA 125000 - THREE-PHASE
TRANSFORMER 400/230V ±5% -
ELECTROSTATIC SHIELD - 125KVA -
IP00**



SKU: 34544
Référence technique: S37B54FDF1000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 125 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP00
Version : with electrostatic shield & regulation tabs ±5%
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 800 W
Load losses : 2850 W
Voltage drop : 2,2 %
UCC : 4,7 %
Efficiency : 97,2 %

DIMENSIONS:

Dimensions (A x B x H) : 640 x 500 x 600 mm
Mounting centres (a x b) : 460 x 320 mm
Mounting diameter (∅) : 14 mm
Weight : 425 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 200A
:
Secondary 230V (gG fuse(s)) : 4 x 315A
Secondary 230V (C circuit breaker(s)) : 4 x 315A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels