






TPA 125000 - ON REQUEST THREE-PHASE TRANSFORMER 125KVA - IP00



SKU: TPA125000_Specific
 Référence technique: S37B54...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 125 kVA
 Primary voltage : max. 1000V
 Secondary voltage : max. 1000V
 :
 Protection : IP00
 Version : specific
 Inrush current : less than or equal to 7 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 800 W
 Load losses : 2850 W
 Voltage drop : 2,2 %
 UCC : 4,7 %
 Efficiency : 97,2 %

DIMENSIONS:

Dimensions (A x B x H) : 640 x 500 x 600 mm
 Mounting centres (a x b) : 460 x 320 mm
 Mounting diameter (ø) : 14 mm
 Weight : 425 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Primary and/or secondary coupling (star, delta, zig-zag)
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Vibration isolating mount
 Running wheels