




TPA 16000 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - 16KVA - IP00



SKU: 34453
Référence technique: A37B45FDF0000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 16 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP00
Version : Transformer (regulation tabs $\pm 5\%$)
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 165 W
Load losses : 890 W
Voltage drop : 5,3 %
UCC : 5,9 %
Efficiency : 93,8 %

DIMENSIONS:

Dimensions (A x B x H) : 490 x 265 x 470 mm
Mounting centres (a x b) : 395 x 235 mm
Mounting diameter (\emptyset) : 11x22 mm
Weight : 82 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 25A
:
Secondary 230V (gG fuse(s)) : 4 x 40A
Secondary 230V (C circuit breaker(s)) : 4 x 40A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels