






TPA 160000 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 160KVA - IP00



SKU: 33553
Référence technique: S37B55FFF0000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 160 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : with regulation tabs $\pm 5\%$
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 880 W
Load losses : 3340 W
Voltage drop : 2 %
UCC : 4,1 %
Efficiency : 97,4 %

DIMENSIONS:

Dimensions (A x B x H) : 720 x 500 x 600 mm
Mounting centres (a x b) : 500 x 360 mm
Mounting diameter (\emptyset) : 14 mm
Weight : 495 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 250A
:
Secondary 400V (gG fuse(s)) : 4 x 250A
Secondary 400V (C circuit breaker(s)) : 4 x 250A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels