




TPA 160000 - ON REQUEST THREE-PHASE TRANSFORMER 160KVA - IP00



SKU: TPA160000_Specific
Référence technique: S37B55...



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 160 kVA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP00
Version : specific
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 880 W
Load losses : 3340 W
Voltage drop : 2 %
UCC : 4,1 %
Efficiency : 97,4 %

DIMENSIONS:

Dimensions (A x B x H) : 720 x 500 x 600 mm
Mounting centres (a x b) : 500 x 360 mm
Mounting diameter (ø) : 14 mm
Weight : 495 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Vibration isolating mount
Runnig wheels