





TPA 16000 - ON REQUEST THREE-PHASE TRANSFORMER 16KVA - IP00



SKU: TPA16000_Specific
Référence technique: A37B45...



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 16 kVA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP00
Version : Transformer (specific)
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 165 W
Load losses : 890 W
Voltage drop : 5,3 %
UCC : 5,9 %
Efficiency : 93,8 %

DIMENSIONS:

Dimensions (A x B x H) : 490 x 265 x 470 mm
Mounting centres (a x b) : 395 x 235 mm
Mounting diameter (∅) : 11x22 mm
Weight : 82 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Vibration isolating mount
Runnig wheels