





**TPA 20000 - THREE-PHASE
TRANSFORMER 400/400V ±5% - 20KVA
- IP00**



SKU: 33463
Référence technique: A37B46FFF0000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 20 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : Transformer (regulation tabs ±5%)
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 99 W
Load losses : 100 W
Voltage drop : 101 %
UCC : 102 %
Efficiency : 103 %

DIMENSIONS:

Dimensions (A x B x H) : 490 x 265 x 470 mm
Mounting centres (a x b) : 395 x 235 mm
Mounting diameter (∅) : 11x22 mm
Weight : 100 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 32A
:
Secondary 400V (gG fuse(s)) : 4 x 32A
Secondary 400V (C circuit breaker(s)) : 4 x 32A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels