


TPA 20000 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - 20KVA - IP00



SKU: 34463
Référence technique: A37B46FDF0000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 20 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP00
Version : Transformer (regulation tabs $\pm 5\%$)
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 210 W
Load losses : 950 W
Voltage drop : 4,5 %
UCC : 5 %
Efficiency : 94,5 %

DIMENSIONS:

Dimensions (A x B x H) : 490 x 265 x 470 mm
Mounting centres (a x b) : 395 x 235 mm
Mounting diameter (\emptyset) : 11x22 mm
Weight : 100 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 32A
:
Secondary 230V (gG fuse(s)) : 4 x 50A
Secondary 230V (C circuit breaker(s)) : 4 x 50A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels