



TPA 200000 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 200KVA - IP00



SKU: 33563
Référence technique: S37B56FFF0000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 200 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : with regulation tabs $\pm 5\%$
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 1070 W
Load losses : 3590 W
Voltage drop : 1,8 %
UCC : 4 %
Efficiency : 97,7 %

DIMENSIONS:

Dimensions (A x B x H) : 745 x 520 x 620 mm
Mounting centres (a x b) : 500 x 360 mm
Mounting diameter (\emptyset) : 14 mm
Weight : 595 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 315A
:
Secondary 400V (gG fuse(s)) : 4 x 315A
Secondary 400V (C circuit breaker(s)) : 4 x 315A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels