




## TPA 200000 - ON REQUEST THREE-PHASE TRANSFORMER 200KVA - IP00



SKU: TPA200000\_Specific  
Référence technique: S37B56...



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 200 kVA  
Primary voltage : max. 1000V  
Secondary voltage : max. 1000V  
:  
Protection : IP00  
Version : specific  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 1070 W  
Load losses : 3590 W  
Voltage drop : 1,8 %  
UCC : 4 %  
Efficiency : 97,7 %

### DIMENSIONS:

Dimensions (A x B x H) : 745 x 520 x 620 mm  
Mounting centres (a x b) : 500 x 360 mm  
Mounting diameter (∅) : 14 mm  
Weight : 595 kg

### PROTECTION(S) RECOMMANDÉE(S):

:  
Other voltages : N.C.

### OPTIONS:

Electrostatic shield  
Thermal sensors (PTC, PT100, Twin-blades)  
Regulation tabs  
Primary and/or secondary coupling (star, delta, zig-zag)  
Dual primary  
Inrush current, frequency, heating, ambient temperature, specific altitude  
Tropicalization  
Vibration isolating mount  
Runnig wheels