




## TPA 25000 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 25KVA - IP00



SKU: 33473  
Référence technique: A37B47FFF0000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 25 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : Transformer (regulation tabs  $\pm 5\%$ )  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 250 W  
Load losses : 1010 W  
Voltage drop : 3,9 %  
UCC : 4,4 %  
Efficiency : 95,2 %

### DIMENSIONS:

Dimensions (A x B x H) : 490 x 240 x 470 mm  
Mounting centres (a x b) : 395 x 235 mm  
Mounting diameter ( $\emptyset$ ) : 11x22 mm  
Weight : 111 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 40A  
:  
Secondary 400V (gG fuse(s)) : 4 x 40A  
Secondary 400V (C circuit breaker(s)) : 4 x 40A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels