


**TPA 25000 - THREE-PHASE
TRANSFORMER 400/230V ±5% -
ELECTROSTATIC SHIELD - 25KVA - IP00**



SKU: 34474
Référence technique: A37B47FDF1000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 25 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP00
Version : Transformer (electrostatic shield & regulation tabs ±5%)
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 250 W
Load losses : 1010 W
Voltage drop : 3,9 %
UCC : 4,4 %
Efficiency : 95,2 %

DIMENSIONS:

Dimensions (A x B x H) : 490 x 265 x 470 mm
Mounting centres (a x b) : 395 x 235 mm
Mounting diameter (∅) : 11x22 mm
Weight : 111 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 40A
:
Secondary 230V (gG fuse(s)) : 4 x 63A
Secondary 230V (C circuit breaker(s)) : 4 x 63A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels