




## TPA 250000 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - 250KVA - IP00



SKU: 34573  
Référence technique: S37B57FDF0000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 250 kVA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP00  
Version : with regulation tabs  $\pm 5\%$   
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 1360 W  
Load losses : 4520 W  
Voltage drop : 1,8 %  
UCC : 5 %  
Efficiency : 97,7 %

### DIMENSIONS:

Dimensions (A x B x H) : 750 x 520 x 740 mm  
Mounting centres (a x b) : 500 x 360 mm  
Mounting diameter ( $\emptyset$ ) : 14 mm  
Weight : 735 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 400A  
:  
Secondary 230V (gG fuse(s)) : 4 x 630A  
Secondary 230V (C circuit breaker(s)) : 4 x 630A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels