


TPA 250000 - ON REQUEST THREE-PHASE TRANSFORMER 250KVA - IP00



SKU: TPA250000_Specific
Référence technique: S37B57...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 250 kVA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP00
Version : specific
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 1360 W
Load losses : 4520 W
Voltage drop : 1,8 %
UCC : 5 %
Efficiency : 97,7 %

DIMENSIONS:

Dimensions (A x B x H) : 750 x 520 x 740 mm
Mounting centres (a x b) : 500 x 360 mm
Mounting diameter (∅) : 14 mm
Weight : 735 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Vibration isolating mount
Runnig wheels