



**TPA 31500 - THREE-PHASE  
TRANSFORMER 400/400V -  
ELECTROSTATIC SHIELD - 31,5KVA -  
IP00**



SKU: 33482  
Référence technique: A37B48FF00000



### CARACTÉRISTIQUES TECHNIQUES:

---

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 31,5 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : Transformer (standard)  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 285 W  
Load losses : 1265 W  
Voltage drop : 3,9 %  
UCC : 4,3 %  
Efficiency : 95,3 %

### DIMENSIONS:

---

Dimensions (A x B x H) : 490 x 370 x 530 mm  
Mounting centres (a x b) : 395 x 340 mm  
Mounting diameter (Ø) : 11x22 mm  
Weight : 138 kg

### PROTECTION(S) RECOMMANDÉE(S):

---

Primary 400V (aM fuse(s)) : 3 x 50A  
:  
Secondary 400V (gG fuse(s)) : 4 x 50A  
Secondary 400V (C circuit breaker(s)) : 4 x 50A

### OPTIONS:

---

Tropicalization  
Vibration isolating mount  
Runnig wheels