



**TPA 315000 - THREE-PHASE  
TRANSFORMER 400/400V -  
ELECTROSTATIC SHIELD - 315KVA -  
IP00**



SKU: 33582  
Référence technique: S37B58FF01000



### **CARACTÉRISTIQUES TECHNIQUES:**

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 315 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : with electrostatic shield  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 1500 W  
Load losses : 5180 W  
Voltage drop : 1,6 %  
UCC : 4,7 %  
Efficiency : 97,9 %

### **DIMENSIONS:**

Dimensions (A x B x H) : 800 x 550 x 740 mm  
Mounting centres (a x b) : 580 x 400 mm  
Mounting diameter (∅) : 14 mm  
Weight : 845 kg

### **PROTECTION(S) RECOMMANDÉE(S):**

Primary 400V (aM fuse(s)) : 3 x 500A  
:  
Secondary 400V (gG fuse(s)) : 4 x 500A  
Secondary 400V (C circuit breaker(s)) : 4 x 500A

### **OPTIONS:**

Tropicalization  
Vibration isolating mount  
Runnig wheels