




TPA 315000 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - ELECTROSTATIC SHIELD - 315KVA - IP00



SKU: 33584
 Référence technique: S37B58FFF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 315 kVA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP00
 Version : with electrostatic shield & regulation tabs $\pm 5\%$
 Inrush current : less than or equal to 7 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 1500 W
 Load losses : 5180 W
 Voltage drop : 1,6 %
 UCC : 4,7 %
 Efficiency : 97,9 %

DIMENSIONS:

Dimensions (A x B x H) : 800 x 550 x 740 mm
 Mounting centres (a x b) : 580 x 400 mm
 Mounting diameter (\varnothing) : 14 mm
 Weight : 845 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 500A
 :
 Secondary 400V (gG fuse(s)) : 4 x 500A
 Secondary 400V (C circuit breaker(s)) : 4 x 500A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Runnig wheels