






## TPA 315000 - ON REQUEST THREE-PHASE TRANSFORMER 315KVA - IP00



SKU: TPA315000\_Specific  
 Référence technique: S37B58...

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 60076  
 Power : 315 kVA  
 Primary voltage : max. 1000V  
 Secondary voltage : max. 1000V  
 :  
 Protection : IP00  
 Version : specific  
 Inrush current : less than or equal to 7 In  
 Heatings : H (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 1500 W  
 Load losses : 5180 W  
 Voltage drop : 1,6 %  
 UCC : 4,7 %  
 Efficiency : 97,9 %

### DIMENSIONS:

Dimensions (A x B x H) : 800 x 550 x 740 mm  
 Mounting centres (a x b) : 580 x 400 mm  
 Mounting diameter (∅) : 14 mm  
 Weight : 845 kg

### PROTECTION(S) RECOMMANDÉE(S):

:  
 Other voltages : N.C.

### OPTIONS:

Electrostatic shield  
 Thermal sensors (PTC, PT100, Twin-blades)  
 Regulation tabs  
 Primary and/or secondary coupling (star, delta, zig-zag)  
 Dual primary  
 Inrush current, frequency, heating, ambient temperature, specific altitude  
 Tropicalization  
 Vibration isolating mount  
 Running wheels