



## TPA 40000 - THREE-PHASE TRANSFORMER 400/230V - 40KVA - IP00



SKU: 34491  
Référence technique: A37B49FD00000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 40 kVA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP00  
Version : Transformer (standard)  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 335 W  
Load losses : 1430 W  
Voltage drop : 3,5 %  
UCC : 4 %  
Efficiency : 95,8 %

### DIMENSIONS:

Dimensions (A x B x H) : 490 x 370 x 530 mm  
Mounting centres (a x b) : 395 x 340 mm  
Mounting diameter (ø) : 11x22 mm  
Weight : 161 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 63A  
:  
Secondary 230V (gG fuse(s)) : 4 x 100A  
Secondary 230V (C circuit breaker(s)) : 4 x 100A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels