



**TPA 400000 - THREE-PHASE  
TRANSFORMER 400/400V ±5% -  
400KVA - IP00**



SKU: 33593  
Référence technique: S37B59FFF0000



### **CARACTÉRISTIQUES TECHNIQUES:**

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 400 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : with regulation tabs ±5%  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 1700 W  
Load losses : 6180 W  
Voltage drop : 1,5 %  
UCC : 4,6 %  
Efficiency : 98,1 %

### **DIMENSIONS:**

Dimensions (A x B x H) : 880 x 650 x 800 mm  
Mounting centres (a x b) : 580 x 400 mm  
Mounting diameter (ø) : 14 mm  
Weight : 1060 kg

### **PROTECTION(S) RECOMMANDÉE(S):**

Primary 400V (aM fuse(s)) : 3 x 630A  
:  
Secondary 400V (gG fuse(s)) : 4 x 630A  
Secondary 400V (C circuit breaker(s)) : 4 x 630A

### **OPTIONS:**

Tropicalization  
Vibration isolating mount  
Runnig wheels