




## TPA 5000 - THREE-PHASE TRANSFORMER 400/230V - 5KVA - IP00



SKU: 34401  
Référence technique: T28B40FD00000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 5 kVA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP00  
Version : Transformer (standard)  
Inrush current : less than or equal to 12 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 85 W  
Load losses : 210 W  
Voltage drop : 4 %  
UCC : 4,1 %  
Efficiency : 94,4 %

### DIMENSIONS:

Dimensions (A x B x H) : 300 x 200 x 310 mm  
Mounting centres (a x b) : 250 x 130 mm  
Mounting diameter (ø) : 11x22 mm  
Weight : 40 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 16A  
:  
Secondary 230V (gG fuse(s)) : 4 x 12A  
Secondary 230V (C circuit breaker(s)) : 4 x 12A

### OPTIONS:

Tropicalization