






TPA 5000 - THREE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 5KVA - IP00



SKU: 34402
Référence technique: T28B40FD01000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 5 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP00
Version : Transformer (electrostatic shield)
Inrush current : less than or equal to 12 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 85 W
Load losses : 210 W
Voltage drop : 4 %
UCC : 4,1 %
Efficiency : 94,4 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 200 x 310 mm
Mounting centres (a x b) : 250 x 130 mm
Mounting diameter (ø) : 11x22 mm
Weight : 40 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 16A
:
Secondary 230V (gG fuse(s)) : 4 x 12A
Secondary 230V (C circuit breaker(s)) : 4 x 12A

OPTIONS:

Tropicalization