



TPA 50000 - THREE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 50KVA - IP00



SKU: 34502
Référence technique: A37B50FD01000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 50 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP00
Version : Transformer (electrostatic shield)
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 405 W
Load losses : 1700 W
Voltage drop : 3,3 %
UCC : 4 %
Efficiency : 96 %

DIMENSIONS:

Dimensions (A x B x H) : 490 x 370 x 580 mm
Mounting centres (a x b) : 395 x 340 mm
Mounting diameter (ø) : 11x22 mm
Weight : 187 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 80A
:
Secondary 230V (gG fuse(s)) : 4 x 125A
Secondary 230V (C circuit breaker(s)) : 4 x 125A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels